

In Screed DSIG-15 Heating Cable

Applications

- Direct acting underfloor heating systems eg. bathrooms
- Background underfloor heating systems
- Best suited for wet areas
- Recommended minimum screed thickness 15mm



The Deviflex™ DSIG-15 is suitable for connection to a continuous 24 hour tariff for underfloor heating, requiring direct or background heating in many residential, commercial and industrial applications.

Typical applications are bathrooms and wet areas or installation over FC sheeting, waterproofing and acoustic underlay.

In Screed DSIG-15 Heating Cable

Features

- 15 W/m makes it suitable for installation over FC sheeting, waterproofing or acoustic insulation
- Flexible
- Thin

Technical Data

Cable construction	Single conductor
Rated voltage	240
Watts per meter	15
Watts per square meter	N/A
Diameter	5.3 ± 0.5mm
Cold Tail Length	3m
Pulling strength	120N
Deformation strength	2,000N
Warranty	10 years
Direct heating in concrete floors	✓
Storage heating in concrete floors	x
Heating in renovated and thin floors	x
Heating in wooden floors	x
Freezers	✓
Ice & snow melting	✓

Stock Program

Code No.	Watts	Length	Cold Tail
84820022	154	11m	1.5mm ²
84820021	193	13m	1.5mm ²
84820020	250	16m	1.5mm ²
84820018	260	17m	1.5mm ²
84820017	335	22m	1.5mm ²
84820016	410	28m	1.5mm ²
84820015	475	31m	1.5mm ²
84820014	570	39m	1.5mm ²
84820019	635	43m	1.5mm ²
84820013	705	48m	1.5mm ²
84820012	865	58m	1.5mm ²
84820011	965	64m	1.5mm ²
84820010	1,140	76m	1.5mm ²
84820009	1,330	89m	1.5mm ²
84820007	1,640	110m	1.5mm ²
84820006	1,785	121m	1.5mm ²
84820005	1,995	133m	1.5mm ²
*153733	2,380	158m	1.5mm ²
*153899	2,890	190m	2.5mm ²
*153857	3,500	230m	2.5mm ²
*153816	4,120	274m	4.0mm ²
*153758	5,180	345m	6.0mm ²
*153733	8,030	535m	6.0mm ²

*Made to order